



INOX

 : Bride tournante

### Raccord à bride tournante douille annelée à collerette

*Swivel flange coupling with serrated tail and collar*  
 Racor con bridas giratorias con collar para manguera

DN bride	DN douille	PN	Référence	P.U. en €
DN15	15mm	10/40	BTDA050SS	
DN20	20mm	10/40	BTDA075SS	
DN25	25mm	10/40	BTDA100SS	
DN32	32mm	10/40	BTDA125SS	
DN40	38mm	10/40	BTDA150SS	
DN50	51mm	10/16	BTDA200SS	
DN65	63mm	10/16	BTDA250SS	
DN80	76mm	10/16	BTDA300SS	
DN100	100mm	10/16	BTDA400SS	
DN150	150mm	10/16	BTDA600SS	
DN200	200mm	10	BTDA800SS	
DN200	200mm	16	BTDA800SS16	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.



INOX

### Raccord à bride fixe douille annelée à collerette

*Fixed flange coupling with serrated tail and collar*  
 Racor con bridas fijas con collar para manguera

DN bride	DN douille	PN	Référence	P.U. en €
DN25	25mm	10/40	BFDA100SS	
DN32	32mm	10/40	BFDA125SS	
DN40	40mm	10/40	BFDA150SS	
DN50	50mm	10/16	BFDA200SS	
DN65	65mm	10/16	BFDA250SS	
DN80	76mm	10/16	BFDA300SS	
DN100	100mm	10/16	BFDA400SS	
DN125	125mm	10/16	BFDA500SS	
DN150	150mm	10/16	BFDA600SS	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.



INOX

### Raccord à bride fixe douille annelée sans collerette

*Fixed flange coupling with serrated tail without collar*  
 Racor con bridas fijas sin collar para manguera

DN bride	DN douille	PN	Référence	P.U. en €
DN40	38mm	10/40	BFDA150SS	
DN50	51mm	10/16	BFDA200SS	
DN65	63mm	10/16	BFDA250SS	
DN80	76mm	10/16	BFDA300SS	
DN100	100mm	10/16	BFDA400SS	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, Brides TTMA.

**Raccord à bride tournante douille lisse à collerette**  
*Swivel flange coupling with smooth tail and collar*  
 Racor con bridas giratorias caña lisa con collar



INOX

 : Bride tournante

DN bride	DN douille	PN	Référence	P.U. en €
DN25	25mm	10/40	BTDL100SS	
DN32	32mm	10/40	BTDL125SS	
DN40	38mm	10/40	BTDL150SS	
DN50	51mm	10/16	BTDL200SS	
DN65	63mm	10/16	BTDL250SS	
DN80	76mm	10/16	BTDL300SS	
DN100	100mm	10/16	BTDL400SS	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.

**Raccord à bride fixe douille lisse à collerette**  
*Fixed flange coupling with smooth tail and collar*  
 Racor con bridas fijas con caña lisa y collar



INOX

DN bride	DN douille	PN	Référence	P.U. en €
DN25	25mm	10/40	BFDL100SS	
DN32	32mm	10/40	BFDL125SS	
DN40	40mm	10/40	BFDL150SS	
DN50	50mm	10/16	BFDL200SS	
DN65	65mm	10/16	BFDL250SS	
DN80	76mm	10/16	BFDL300SS	
DN100	100mm	10/16	BFDL400SS	
DN125	125mm	10/16	BFDL500SS	
DN150	150mm	10/16	BFDL600SS	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.

**Bride à collerette PN 10/16 à souder**  
*Plane flange with collar for welding*  
 Brida llana con collar para soldar



INOX

DN bride	Dim partie à souder	PN	Référence	P.U. en €
DN15	21.3mm	10/40	BPC050SS	
DN20	26.9mm	10/40	BPC075SS	
DN25	33.7mm	10/40	BPC100SS	
DN32	42.4mm	10/40	BPC125SS	
DN40	48.3mm	10/40	BPC150SS	
DN50	60.3mm	10/16	BPC200SS	
DN65	76.1mm	10/16	BPC250SS	
DN80	88.9mm	10/16	BPC300SS	
DN100	114.3mm	10/16	BPC400SS	
DN125	139.7mm	10/16	BPC500SS	
DN150	168.3mm	10/16	BPC600SS	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs.



INOX

**Bride plate type 02A - NF EN 1092-1**  
Plane flange  
Brida llana

DN	Pression nominale	Référence	P.U. en €
DN15	10/40	BP050SS	
DN20	10/40	BP075SS	
DN25	10/40	BP100SS	
DN32	10/40	BP125SS	
DN40	10/40	BP150SS	
DN50	10/16	BP200SS	
DN65	10/16	BP250SS	
DN80	10/16	BP300SS	
DN100	10/16	BP400SS	
DN125	10/16	BP500SS	
DN150	10/16	BP600SS	
DN200	10	BP800SS	
DN200	16	BP800SS16	



INOX

**Bride plate ASA ASME B 16.5**  
Restrained flange  
Brida tapón


Ø	Pression nominale	Référence	P.U. en €
DN15	20 Bar / 150lbs	BP050SS150	
	50 Bar / 300lbs	BP050SS300	
DN20	20 Bar / 150lbs	BP075SS150	
	50 Bar / 300lbs	BP075SS300	
DN25	50 Bar / 300lbs	BP100SS300	
	DN32	20 Bar / 150lbs	BP125SS150
50 Bar / 300lbs		BP125SS300	
DN40	100 Bar / 600lbs	BP125SS600	
	20 Bar / 150lbs	BP150SS1500	
	50 Bar / 300lbs	BP150SS300	
DN50	100 Bar / 600lbs	BP150SS600	
	20 Bar / 150lbs	BP200SS150	
	50 Bar / 300lbs	BP200SS300	
DN80	20 Bar / 150lbs	BP300SS150	
	50 Bar / 300lbs	BP300SS300	
DN100	20 Bar / 150lbs	BP400SS150	
DN125	20 Bar / 150lbs	BP500SS150	
DN150	20 Bar / 150lbs	BP600SS150	

**Bride pleine tampon type 05A - NF EN 1092-1**  
*Restrain flange*  
 Brida tapón


INOX

DN	Pression nominale	Référence	P.U. en €
DN15	10/40	BT050SS	
DN25	10/40	BT100SS	
DN32	10/40	BT125SS	
DN40	10/40	BT150SS	
DN50	10/16	BT200SS	
DN65	10/16	BT250SS	
DN80	10/16	BT300SS	
DN100	10/16	BT400SS	

❗ Disponibles sur demande : brides embouties point bleu, brides TTMA.

**Bride pleine tampon ASA ASME B 16.5**  
*Restrain flange*  
 Brida tapón


INOX

Ø	Pression nominale	Référence	P.U. en €
DN20	50 Bar / 300lbs	BT075SSASA300	
DN150	20 Bar / 150lbs	BT600SS150	



ACIER

 : Bride tournante

**Raccord à bride tournante douille annelée à collerette**  
*Swivel flange coupling with serrated tail and collar*  
 Racor con bridas giratorias con collar para manguera

DN bride	DN douille	PN	Référence	P.U. en €
DN15	15mm	10/40	BTDA050AC	
DN20	20mm	10/40	BTDA075AC	
DN25	25mm	10/40	BTDA100AC	
DN32	32mm	10/40	BTDA125AC	
DN40	38mm	10/40	BTDA150AC	
DN50	50mm	10/16	BTDA200AC	
DN65	63mm	10/16	BTDA250AC	
DN80	76mm	10/16	BTDA300AC	
DN80	80mm	10/16	BTDA325AC	
DN100	100mm	10/16	BTDA400AC	
DN150	150mm	10/16	BTDA600AC	
DN200	200mm	10	BTDA800AC	

! Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.



ACIER

**Raccord à bride fixe douille annelée à collerette**  
*Fixed flange coupling with serrated tail and collar*  
 Racor con bridas fijas con collar para manguera

DN bride	DN douille	PN	Référence	P.U. en €
DN20	20mm	10/40	BFDA075AC	
DN25	25mm	10/40	BFDA100AC	
DN32	32mm	10/40	BFDA125AC	
DN40	38mm	10/40	BFDA150AC	
DN50	50mm	10/16	BFDA200AC	
DN65	65mm	10/16	BFDA250AC	
DN80	76mm	10/16	BFDA300AC	
DN100	100mm	10/16	BFDA400AC	
DN125	125mm	10/16	BFDA500AC	
DN150	150mm	10/16	BFDA600AC	

! Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.



ACIER

**Raccord à bride fixe douille annelée sans collerette**  
*Fixed flange coupling with serrated tail without collar*  
 Racor con bridas fijas sin collar para manguera

DN bride	DN douille	PN	Référence	P.U. en €
DN25	25mm	10/40	100FP	
DN32	32mm	10/40	125FP	
DN40	38mm	10/40	150FP	
DN50	51mm	10/40	200FP	
DN65	63mm	10/16	250FP	
DN80	76mm	10/16	300FP	
DN100	100mm	10/16	400FP	
DN125	125mm	10/16	500FP	
DN150	150mm	10/16	600FP	

! Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.

**Raccord à bride tournante douille lisse à collerette**  
*Swivel flange coupling with smooth tail and collar*  
 Racor con bridas giratorias caña lisa con collar



ACIER

 : Bride tournante

DN bride	DN douille	PN	Référence	P.U. en €
DN25	25mm	10/40	BTDL100AC	
DN32	32mm	10/40	BTDL125AC	
DN40	38mm	10/40	BTDL150AC	
DN50	51mm	10/16	BTDL200AC	
DN65	63mm	10/16	BTDL250AC	
DN80	76mm	10/16	BTDL300AC	
DN100	100mm	10/16	BTDL400AC	
DN125	125mm	10/16	BTDL500AC	
DN150	150mm	10/16	BTDL600AC	
DN200	200mm	10	BTDL800AC	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.

**Raccord à bride fixe douille lisse à collerette**  
*Fixed flange coupling with smooth tail and collar*  
 Racor con bridas fijas con caña lisa y collar



ACIER

DN bride	DN douille	PN	Référence	P.U. en €
DN40	38mm	10/40	BFDL150AC	
DN50	50mm	10/16	BFDL200AC	
DN65	65mm	10/16	BFDL250AC	
DN80	76mm	10/16	BFDL300AC	
DN100	100mm	10/16	BFDL400AC	
DN125	125mm	10/16	BFDL500AC	
DN150	150mm	10/16	BFDL600AC	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.

**Bride à collerette PN 10/16 à souder**  
*Plane flange with collar for welding*  
 Brida llana con collar para soldar



ACIER

DN bride	Dim partie à souder	PN	Référence	P.U. en €
DN15	21.3mm	10/40	BPC050AC	
DN20	26.9mm	10/40	BPC075AC	
DN25	33.7mm	10/40	BPC100AC	
DN32	42.4mm	10/40	BPC125AC	
DN40	48.3mm	10/40	BPC150AC	
DN50	60.3mm	10/16	BPC200AC	
DN65	76.1mm	10/16	BPC250AC	
DN80	88.9mm	10/16	BPC300AC	
DN100	114.3mm	10/16	BPC400AC	
DN125	139.7mm	10/16	BPC500AC	
DN150	168.3mm	10/16	BPC600AC	
DN200	219.1mm	10	BPC800AC	

 Disponibles sur demande : brides ASA 150 lbs - ASA 300 lbs, brides embouties point bleu, brides TTMA.



ACIER



### Bride plate type 02A - NF EN 1092-1

*Plane flange*  
Brida llana

DN	Pression nominale	Référence	P.U. en €
DN15	10/40	BP050AC	
DN20	10/40	BP075AC	
DN25	10/40	BP100AC	
DN32	10/40	BP125AC	
DN40	10/40	BP150AC	
DN50	10/16	BP200AC	
DN65	10/16	BP250AC	
DN80	10/16	BP300AC	
DN100	10/16	BP400AC	
DN125	10/16	BP500AC	
DN150	10/16	BP600AC	
DN200	10	BP800AC	
DN200	16	BP800AC16	



ACIER



### Bride plate ASA ASME B 16.5

*Plane flange*  
Brida llana

Ø	Pression nominale	Référence	P.U. en €
DN20	20 Bar / 150lbs	BP075AC150	
	50 Bar / 300lbs	BP075AC300	
DN25	20 Bar / 150lbs	BP100AC150	
	50 Bar / 300lbs	BP100AC300	
DN32	20 Bar / 150lbs	BP125AC150	
	50 Bar / 300lbs	BP125AC300	
DN40	20 Bar / 150lbs	BP150AC150	
	50 Bar / 300lbs	BP150AC300	
DN50	20 Bar / 150lbs	BP200AC150	
	50 Bar / 300lbs	BP200AC50	
DN65	20 Bar / 150lbs	BP250AC150	
	50 Bar / 300lbs	BP250AC300	
DN80	20 Bar / 150lbs	BP300AC150	
	50 Bar / 300lbs	BP300AC300	
DN100	20 Bar / 150lbs	BP400AC150	
	50 Bar / 300lbs	BP400AC300	
DN125	20 Bar / 150lbs	BP500AC150	
	50 Bar / 300lbs	BP500AC300	
DN150	20 Bar / 150lbs	BP600AC150	
	50 Bar / 300lbs	BP600AC300	
DN200	20 Bar / 150lbs	BP800AC150	
DN250	20 Bar / 150lbs	BP1000AC150	



### Bride pleine tampon type 05A NF EN 1092-1

*Restrained flange*  
Brida tapón



DN	Pression nominale	Référence	P.U. en €
DN15	10/40	BT050AC	
DN25	10/40	BT075AC	
DN25	10/40	BT100AC	
DN32	10/40	BT125AC	
DN40	10/40	BT150AC	
DN50	10/16	BT200AC	
DN65	10/16	BT250AC	
DN80	10/16	BT300AC	
DN100	10/16	BT400AC	



ACIER

### Bride pleine tampon ASA ASME B 16.5

*Restrained flange*  
Brida tapón



Ø	Pression nominale	Référence	P.U. en €
DN25	20 Bar / 150lbs	BT100AC150	
DN40	50 Bar / 300lbs	BT150AC300	
DN50	20 Bar / 150lbs	BT200AC150	
DN65	20 Bar / 150lbs	BT250AC150	
DN80	20 Bar / 150lbs	BT300AC150	
DN100	20 Bar / 150lbs	BT400AC150	
DN125	20 Bar / 150lbs	BT500AC150	
DN150	20 Bar / 150lbs	BT600AC150	
DN200	20 Bar / 150lbs	BT800AC150	
DN250	20 Bar / 150lbs	BT1000AC150	



ACIER

### Joint de brides

*Gaskets for flanges*  
Juntas para bridas



DN Raccord	Ø Joint	Epaisseur	Référence	P.U. en €
DN15	51 X 27	2	JB015	
DN20	61 X 33	2	JB020	
DN25	71 X 40	2	JB025	
DN32	82 X 48	2	JB032	
DN40	92 X 54	2	JB040	
DN50	107 X 66	2	JB050	
DN65	127 X 82	2	JB065	
DN80	142 X 95	2	JB080	
DN100	162 X 120	2	JB100	
DN125	192 X 148	2	JB125	
DN150	218 X 176	2	JB150	
DN200	273 X 229	2	JB200	
DN250	384 X 332	2	JB250	
DN300	384 X 332	2	JB300	
DN350	444 X 371	2	JB350	
DN400	495 X 423	2	JB400	







ALUMINIUM



**Mamelon mâle/mâle BSP**  
*Nipple male/male BSP*  
 Doble rosca macho/macho BSP

Filetage 1	Filetage 2	Référence	P.U. en €
1"1/2	1"1/4	MM150125AL	
1"1/2	1"1/2	MM150150AL	
2"	1"1/2	MM200150AL	
2"	2"	MM200200AL	
2"1/2	2"	MM250200AL	
2"1/2	2"1/2	MM250250AL	
3"	2"	MM300200AL	
3"	2"1/2	MM300250AL	
3"	3"	MM300300AL	
4"	3"	MM400300AL	
4"	4"	MM400400AL	
5"	5"	MM500500AL	
6"	6"	MM600600AL	

! Autres dimensions disponibles sur demande.



ALUMINIUM



**Mamelon femelle/femelle BSP**  
*Nipple female/female BSP*  
 Doble rosca hembra/hembra BSP

Taraudage 1	Taraudage 2	Référence	P.U. en €
1"	3/4"	FF100075AL	
1"1/2	1"1/2	FF150AL	
2"	1"1/2	FF200150AL	
2"	2"	FF200AL	
2"1/2	2"	FF250200AL	
2"1/2	2"1/2	FF250AL	
3"	2"	FF300200AL	
3"	2"1/2	FF300250AL	
3"	3"	FF300AL	
4"	2"	FF400200AL	
4"	2"1/2	FF400250AL	
4"	3"	FF400300AL	
4"	4"	FF400AL	
5"	4"	FF500400AL	
5"	5"	FF500AL	
6"	5"	FF600500AL	



**Raccord à bride tournante douille annelée à collerette**  
*Swivel flange coupling with serrated tail and collar*  
 Racor con bridas giratorias con collar para manguera



DN bride	DN douille	PN	Référence	P.U. en €
DN50	51mm	10	BTDA200PP	
DN80	76mm	10	BTDA300PP	



POLYPROPYLÈNE

**Raccord à bride tournante douille lisse à collerette**  
*Swivel flange coupling with smooth tail and collar*  
 Racor con bridas giratorias caña lisa con collar



DN bride	DN douille	PN	Référence	P.U. en €
DN40	38mm	10	BTDL150PP	
DN50	51mm	10	BTDL200PP	
DN80	76mm	10	BTDL300PP	
DN100	100mm	10	BTDL400PP	



POLYPROPYLÈNE

**Bride plate**  
*Plane flange*  
 Brida llana



Ø	Pression nominale	Référence	P.U. en €
DN40	10	BP150PP	
DN50	10	BP200PP	
DN80	10	BP300PP	
DN100	10	BP400PP	



POLYPROPYLÈNE